

## Hot-Melt Glue Gun AS-5020 – without compressed air



The glue gun AS-5020 allows the handling of high- and low viscous hot melt adhesives of almost all types **without the usage of compressed air**. The application can be dots or line type.

The AS-5020 model does **not need any compressed air** and due to 500W power input the glue gun is ready for use within approximately 5 minutes. The thermostat-controlled temperature adjustment control unit has been integrated into the (upper) body of the glue gun to complete the functional design. It ensures the optimal handling temperature of the hot melt adhesives (no coking/ cracking).

The adjustable trigger and the ergonomic body design enable the user to work fatigue-proof and comfortable. The magnetic stand assures the secure placing of the device.

The large filler opening facilitates the easy and clean refilling of the hot melt cylinder.

## Technical Data

### AS-5020

Weight	1220g
Power Supply	230 V / 50 Hz
Power Consumption	500 Watt
Current Consumption	2,6 A
Degree of protection	I
Class of protection	IP 30
Temperature control	Thermostat
Temperature limitation	Temperature monitor
Operating temperature	20-200°C
Consistency of temperature	+/- 5°C
Heat-up-time	approx. 5 min.
GrossTank Capacity	250 ml
Conveying system	Mechanics
Length of electric cord	1,8 m
Recommended melts	Hot-melt granulate, pillows and 43mm slugs

**Stand \*\***



**\*\* included in delivery**