

Hot-Melt Glue Guns AS-5050-P/5055-P-LCD



The glue guns AS-5050/5055 allow the handling of high- and low viscous hot melt adhesives without the usage of any dissolver. The application can be dots or line type.

The workstation (**not included in the scope of delivery**) comes with an integrated pneumatic stabilizer as well as a manometer display. The fine tuning of the compressed air guarantees an optimal and exact hot melt application. The manometer display enables the user to adjust and control the preset air pressure at all times.

The electronic (AS-5055) and thermostat-controlled (AS-5050) temperature adjustment control unit has been integrated into the grip to complete the functional design of the glue gun. It ensures the optimal handling temperature of the hot melt adhesives (no coking/ cracking).

Both, the digital (AS-5055) as well as the analog (AS-5050), temperature display exactly show the preset temperature at all times during the handling process.

Technical Data

	AS-5050-P	AS-5055-P-LCD
Weight	1200g	1400g
Power Supply	230 V / 50 Hz	230 V / 50 Hz
Power Consumption	600 Watt	600 Watt
Current Consumption	1,75 A	1,75 A
Degree of protection	I	I
Class of protection	IP 30	IP 30
Temperature control	Thermostat	Electronic
Temperature limitation	Temperature monitor	Temperature monitor
Operating temperature	20-200°C	50-210°C
Consistency of temperature	+ /- 5°C	+/- 2°C
Temperature indication	analog	digital
Heat-up-time	approx. 3-10 min.	approx. 3-10 min.
GrossTank Capacity	250 ml	330 ml
Conveying system	Air pressure	Air pressure
Operating pressure	0,5 - 6 bar	0,5 - 6 bar
Length of electric cord	8,5 m	8,5 m
Recommended melts	Hot-melt granulate, pillows and 43mm slugs	Hot-melt granulate, pillows and 43mm slugs

AS-Workstation *



* not included in delivery