

Cartridge Glue Gun AS-5070-P-LCD



The cartridge glue gun AS-5070-P-LCD allows the handling of high- and low viscous PUR-hot melt adhesives in 310ml AL cartridges without the usage of any dissolver. The application can be dots or line type.

The workstation (**not included in the scope of delivery**) comes with an integrated pneumatic stabilizer as well as a manometer display. The fine tuning of the compressed air guarantees an optimal and exact hot melt application. The manometer display enables the user to adjust and control the preset air pressure at all times.

The electronic temperature adjustment control unit has been integrated into the grip to complete the functional design of the glue gun. It ensures the optimal handling temperature of the PUR- hot melt adhesives (no coking/ cracking).

The digital temperature display (LCD) shows the preset temperature at all times during the handling process.

Technical Data

AS-5070-P-LCD

Weight	1400g
Power Supply	230 V / 50 Hz
Power Consumption	600 Watt
Current Consumption	1,75 A
Degree of protection	I
Class of protection	IP 30
Temperature control	Electronic
Temperature limitation	Temperature monitor
Operating temperature	50-210°C
Consistency of temperature	+ /- 2°C
Temperature indication	digital
Heat-up-time	approx. 3-10 min.
GrossTank Capacity	310 ml
Conveying system	Air pressure
Operating pressure	0,5 - 6 bar
Length of electric cord	8,5 m
Recommended melts	310 ml hot-melt cartridges

AS-Workstation*



* not included in delivery